

Especificaciones



Eaton FRN-R-30

Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 30 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series FRN-R fuse
CATALOG NUMBER	FRN-R-30
UPC	051712101769
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.05 lb
COMPLIANCES	CE Marked

Especificaciones del producto

AMPERAGE RATING	30 A
NUMBER OF ELEMENTS	Dual
OPERATING TEMPERATURE	-60 °C to +100 °C
CLASS	Class RK5
INTERRUPT RATING	200 kAIC at 250 Vac 20 kAIC at 125 Vdc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	8 sec at 500%
PACKAGING TYPE	Standard
VOLTAGE RATING	250 Vac, 125 Vdc
TYPE	Current-limiting time-delay fuse
SPECIAL FEATURES	Finger safe
APPLICATION	Combination starters, motor control centers, machinery disconnects, power panelboards

Recursos

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2025 Eaton. Todos los derechos reservados.

Follow us on social media to get the latest product and support information.

