

Especificaciones



La foto es representativa



Eaton FRS-R-45

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 45 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 250 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series FRS-R fuse
CATALOG NUMBER	FRS-R-45
UPC	051712508377
PRODUCT LENGTH/DEPTH	5.5 in
PRODUCT HEIGHT	1.84 in
PRODUCT WIDTH	1.84 in
PRODUCT WEIGHT	0.293 lb
COMPLIANCES	CE Marked



Powering Business Worldwide

Especificaciones del producto

AMPERAGE RATING	45 A
NUMBER OF ELEMENTS	Dual
CLASS	Class RK5
INTERRUPT RATING	20 kAIC at 250 Vdc 200 kAIC at 600 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	10 sec at 500%
PACKAGING TYPE	Standard
VOLTAGE RATING	600 Vac, 250 Vdc
TYPE	Current-limiting time-delay fuse
APPLICATION	Combination starters, motor control centers, machinery disconnects, power panelboards

Recursos

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.