

Especificaciones



Eaton FWA-60A21F

Eaton Bussmann series FWA high speed fuse, 500 Vac/dc (35-800A only), 60A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWA-60A21F
UPC	051712795296
EAN	5027590499309
PRODUCT LENGTH/DEPTH	62 mm
PRODUCT HEIGHT	47 mm
PRODUCT WIDTH	110 mm
PRODUCT WEIGHT	56.3 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized



Powering Business Worldwide

Especificaciones del producto

AMPERAGE RATING	60 A
BREAKING CAPACITY	200 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
FUSE INDICATOR	Other
RELEASE CHARACTERISTIC	Other
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
FUSE SIZE	21 x 51 mm
RATED VOLTAGE AC	150 V
RATED VOLTAGE DC	150 V
CLASS	Class aR
CLEARING (I2T)	2400 at 150 V
WATT LOSSES	8 W
FUSE SHAPE	Cylindrical
PRE ARC (I2T)	250
INTERRUPT RATING	100 kAIC
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	Other
MATERIAL	Ceramic
PACKAGING TYPE	Standard
VOLTAGE RATING	150 V
TYPE	High speed fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
FUSE TYPE	FWA-A21F
BREAKING CAPACITY AT NOMINAL VOLTAGE, AC	200 kA
BREAKING CAPACITY AT NOMINAL VOLTAGE, DC	50 kA

Recursos

MCAD MODEL	eaton-hs-round-body-fuses-mcad-3d-models-fwa-35-60a-21f.stp
------------	---

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.